

## M10-AD22 SERIES



### Features

- .AC and DC combined power supply
- .DC constant voltage and constant current
- .AC output over load protection
- .19-inch rack mount (3U) and benchtop
- .Output from front panel and rear panel
- .Temperature controlled fan

### Specifications

#### DC output

- .Line Regulation: CV  $1 \times 10^{-4} + 3\text{mV}$  CC  $2 \times 10^{-3} + 3\text{mA}$   
Fixed output 10mV
- .Load Regulation: CV  $1 \times 10^{-4} + 5\text{mV}$  CC  $2 \times 10^{-3} + 5\text{mA}$   
Fixed output 10mV
- .Ripple & Noise: CV 1mVrms CC 3mArms  
Fixed output 10mV
- .Fixed Output Accuracy: 2.5%
- .Display Accuracy: Voltmeter  $\pm(0.2\% \text{Rdg} + 2\text{digits})$   
Ammeter  $\pm(1.0\% \text{Rdg} + 2\text{digits})$

#### AC output

- .Display Accuracy: Voltmeter  $\pm(1.0\% \text{Rdg} + 2\text{digits})$   
Ammeter  $\pm(1.0\% \text{Rdg} + 2\text{digits})$
- .Input Voltage: 110~127VAC  $\pm 10\%$ , 220~240VAC  $\pm 10\%$  Switchable

Model	DC Output Voltage	DC Output Current	AC Output Voltage	AC Output Current	Size	Weight (kg)
M10-AD2205	0-30V,5V	0-5A,3A	0-250V	2.5A	19" 3U	14
M10-AD2210	0-30V,5V	0-5A,3A	0-250V	4.5A	19" 3U	16



**M10-AD2210**

AZIENDA CERTIFICATA



Note: all features are subject to change without notice.