

M10-QD SERIES



NEW

Features

- . **Output off function**
- . **Dual independent adjustable DC outputs.**
- . Independent, series and parallel variety output
- . Constant voltage and constant current
- . Low ripple and noise
- . Four LED displays with 3 digits, selectable for two sets output voltage and current display simultaneously
- . 16 hours continuous output with full load
- . Auto tracking output



M10-QD305

Specifications

- . Line regulation: CV $1 \times 10^{-4} + 3\text{mV}$ CC $2 \times 10^{-3} + 3\text{mA}$
- . Load regulation: CV $1 \times 10^{-4} + 4\text{mV}$ CC $2 \times 10^{-3} + 5\text{mA}$
- . Ripple & noise: CV 1mV rms CC 3mA rms
- . Display accuracy: $\pm 0.5\% \text{Rdg} + 2\text{digits}$
- . Input voltage: 110~127VAC $\pm 10\%$, 220~240 $\pm 10\%$ Switchable

Model	Independent Output	Series Output	Parallel Output	Dimensions (W×H×D)	Weight (kg)
M10-QD302	CH1 0~30V/0~2A CH2 0~30V/0~2A	CH1+CH2 0~60V/0~2A	CH1//CH2 0~30V/0~4A	250×135×300 mm	7.8
M10-QD303	CH1 0~30V/0~3A CH2 0~30V/0~3A	CH1+CH2 0~60V/0~3A	CH1//CH2 0~30V/0~6A	250×135×300 mm	7.8
M10-QD305	CH1 0~30V/0~5A CH2 0~30V/0~5A	CH1+CH2 0~60V/0~5A	CH1//CH2 0~30V/0~10A	250×135×300 mm	7.8
M10-QD3010	CH1 0~30V/0~10A CH2 0~30V/0~10A	CH1+CH2 0~60V/0~10A	CH1//CH2 0~30V/0~20A	250×135×460 mm	12
M10-QD3020	CH1 0~30V/0~20A CH2 0~30V/0~20A	CH1+CH2 0~60V/0~20A	CH1//CH2 0~30V/0~40A	250×135×460 mm	16
M10-QD6010	CH1 0~60V/0~10A CH2 0~60V/0~10A	CH1+CH2 0~120V/0~10A	CH1//CH2 0~60V/0~20A	250×135×460 mm	16



Conformi a:
 Direttive CEE: 73/23 - 93/68 - 89/336
 Norme Cenelec: EN 55011 cl. A, EN 61000-6-4, EN 61000-4-4, EN 61000-4-2, EN 61000-4-3, EN 61558-2-6



Note: all features are subject to change without notice.